

## Solvent for cleaning road marking equipment

### Solvent for cleaning application equipment

**Symbol :** 24.30.22-79.31  
**Standard:** WT-1034-2007

<b>Range of application:</b>	The solvent is used to clean equipment and tools used for applying solvent-based paints and chemically-cured materials.
<b>Functional properties:</b>	The solvent is a clear and uniform substance free of any contamination and water. <b>General technical information:</b> c) density g/cm <sup>3</sup> 0,86 ± 0,02      PN-90/C-04004 pt. 2.1
<b>Application method:</b>	Once the paint or material application process is finished, all the equipment used in the operation should be cleaned using the solvent. The volume of the solvent used depends on the type and kind of equipment. <b>Do not thin solvent-based paints using the solvent as this will lead to a significant decrease in the quality of the paint.</b>
<b>Packaging:</b>	30 l non-returnable plastic canisters.
<b>Warranty:</b>	24 months from the production date if stored in its original packaging and not exposed to direct sunlight.
<b>H&amp;S and fire safety guidelines:</b>	The solvent contains highly flammable volatile substances. It should be used in well ventilated areas. Store in tightly sealed packagings away from sources of fire and heat. For more detailed information refer to the Material Safety Data Sheet.

## Solvent for cleaning road marking equipment