

## WPZ 11 solvent

### for road marking paints

**Symbol :** 24.30.22-79.31  
**Standard:** ZN-PCW-1369:2004

<b>Range of application:</b>	The solvent is used for thinning road marking paints to the required viscosity and for cleaning equipment and tools used for applying paints and chemically-cured materials.																		
<b>Functional properties:</b>	<p>The solvent is a clear and uniform substance free of any contamination and water.</p> <p><b>General technical information:</b></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">Volatility compared to acetone</td> <td style="width: 20%;"></td> <td style="width: 30%; text-align: right;">&lt; 8</td> </tr> <tr> <td>Density in 20°C</td> <td style="text-align: right;">[g/cm<sup>3</sup>]</td> <td style="text-align: right;">0,86-0,87</td> </tr> <tr> <td>Flashpoint</td> <td style="text-align: right;">[°C]</td> <td style="text-align: right;">≥ 5</td> </tr> <tr> <td>Boiling temp. range</td> <td></td> <td></td> </tr> <tr> <td style="padding-left: 20px;">– start</td> <td style="text-align: right;">[°C]</td> <td style="text-align: right;">≥ 108</td> </tr> <tr> <td style="padding-left: 20px;">– 92% of the product distils to a temp. of</td> <td style="text-align: right;">[°C]</td> <td style="text-align: right;">≤ 120</td> </tr> </table>	Volatility compared to acetone		< 8	Density in 20°C	[g/cm <sup>3</sup> ]	0,86-0,87	Flashpoint	[°C]	≥ 5	Boiling temp. range			– start	[°C]	≥ 108	– 92% of the product distils to a temp. of	[°C]	≤ 120
Volatility compared to acetone		< 8																	
Density in 20°C	[g/cm <sup>3</sup> ]	0,86-0,87																	
Flashpoint	[°C]	≥ 5																	
Boiling temp. range																			
– start	[°C]	≥ 108																	
– 92% of the product distils to a temp. of	[°C]	≤ 120																	
<b>Application method:</b>	<b>Add the solvent to the paint in small portions of 3% w/w</b> while carefully stirring until the desired viscosity is obtained.																		
<b>Packaging:</b>	Non-returnable 20 kg steel drums.																		
<b>Warranty:</b>	24 months from the production date if stored in its original packaging and not exposed to direct sunlight.																		
<b>H&amp;S and fire safety guidelines:</b>	The solvent contains highly flammable volatile substances. It should be used in well ventilated areas. Store in tightly sealed packagings away from sources of heat or fire For more detailed information refer to the Material Safety Data Sheet.																		

## WPZ 11 solvent